



PRODUCT-DETAILS

UK662CV

Combi Unit UK600 Combi, Flush-/ hollow wall mounting, 24 modules, 5 row(s), IP30, Door: Single, Steel Sheet, Dimensions: 872 mm x 384 mm x 97 mm



General Information	
Extended Product Type	UK662CV
Product ID	2CPX031398R9999
EAN	4011617313984
Catalog Description	Combi Unit UK600 Combi, Flush-/ hollow wall mounting, 24 modules, 5 row(s), IP30, Door: Single, Steel Sheet, Dimensions: 872 mm x 384 mm x 97 mm
Long Description	Combi Unit, series UK600, Expansion option: Lateral and bottom, for the internal use, with closed doorframe and door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, Impact strength IK07, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, Powder-coated, in RAL 9016, enclosure out of thermoplast, with frame and ventilated door , door out of sheet steel, in RAL 9016, with TIP-in closure, door opening angle 120 degree, door hinge right or left, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 872 x 384 x 97, Shutter frame dimensions in mm (H x W x D): 872 x 384 x 9, Space units 24, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, with N/PE without terminal, cable fastening rail integrated, assembled with device carrier, segregation wall, perforated sheet steel mounting plate and socket outlet, device support removable

Technical

Number of Rows	5
Closure Type	Push Button
Configuration Type	assembled with device carrier, segregation wall, perforated sheet steel mounting plate and socket outlet
Cover Plate Type	Door
Enclosure Type	Combi Unit
Door Type	Single
Accessories Available	Yes
DIN Place Units	24
Terminal Type	No Terminals
Impact Resistance Rating	IK07

Electrical

Rated Operational Voltage	Maximum 400 V
Operational Voltage	400 V
Rated Current (I _N)	63 A
Power Loss	Δt = 30K 78 W

Design

Surface Finishing	Powder-coated
Housing Material	Plastic
Door Material	Steel Sheet
Cover Style	Closed
RAL Number	RAL 9016 - Traffic White
Color	Traffic white
Number of Modules	24

Material Compliance

RoHS Declaration	2CPC100018X0201
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20240903
REACH Declaration	2CPC100005X0201
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20240902
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Environmental

Degree of Protection	IP30
Protection Class	Isolated (Class II)

Dimensions

Width in Number of Modular Spacings	12
Product Net Width	384 mm
Product Net Height	872 mm
Product Net Depth / Length	97 mm
Product Net Weight	5.519 kg
Built-In Depth (t ₂)	88 mm
Dimension Diagram	2CPC000001D0201 2CPC000004D0201 2CPC000005D0201 2CPC000007D0201

Engineering

Building Information Modeling – BIM	9AKK107046A7947
-------------------------------------	-----------------

Ordering

Package Level 1 Units	pack 1 piece
Package Level 1 Gross Weight	5.74 kg
E-Number (Sweden)	2201246

Certificates and Declarations

Declaration of Conformity - CE	2CPC100018X0201
--------------------------------	-----------------

Installation

Instructions and Manuals	2CPC130100M5601 2CPC130110M5601
Mounting Type	Flush-/ hollow wall mounting

Popular Downloads

Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101
-----------------------------------	------------------------------------

External Classifications and Standards

ETIM 9	EC000214 - Small distribution board
ETIM 10	EC000214 - Small distribution board
eClass	V11.0 : 27142409
Object Classification Code	U
Standards	DIN 43871

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CPX062745R9999	Quick terminals terminals , blue , N/RDC Terminal , Quick-Terminal	ZK50BT	1	piece
2CPX030892R9999	Enclosure accessories UK600 / AK600 accessories, Direct mounting, IP30, Dimensions: 36 mm x 42 mm x 15 mm	ZK507	1	piece
2CPX031413R9999	Enclosure accessories UK600 / AK600 accessories, Door: Single, Dimensions: 43 mm x 59 mm x 41 mm	UZT4	1	piece
2CPX031412R9999	Enclosure accessories UK600 / AK600 accessories, Door: Single, Dimensions: 43 mm x 59 mm x 41 mm	UZT3	1	piece
2CPX031434R9999	Enclosure accessories UK600 accessories, Dimensions: 80 mm x 120 mm x 30 mm	UZ91P4	1	piece
2CPX031406R9999	Enclosure accessories UK600 accessories, 60 modules, 5 row(s), Dimensions: 872 mm x 384 mm x 90 mm	AP660	1	piece
2CPX061178R9999	Interior fitting system Accessories Media, Dimensions: 62 mm x 125 mm x 68 mm	ZX29	1	piece
2CPX061177R9999	Customized electrical components Accessories Media, Dimensions: 50 mm x 102 mm x 63 mm	ZE225	1	piece
2CPX031408R9999	Enclosure accessories UK600 accessories, Dimensions: 109 mm x 109 mm x 36 mm	UZB2	1	piece
2CPX061211R9999	Customized electrical components Accessories Media, Dimensions: 63 mm x 213 mm x 58 mm	ZE227	1	piece
2CPX031426R9999	Interior fitting system Accessories Media, Dimensions: 40 mm x 16 mm x 63 mm	ZE338	1	piece
2CPX031427R9999	Customized electrical components Accessories Media, Dimensions: 54 mm x 50 mm x 58 mm	ZE224	1	piece
2CPX031424R9999	Interior fitting system Accessories Media, 12 modules, Dimensions: 53 mm x 246 mm x 63 mm	ZE336	1	piece
2CPX031423R9999	Interior fitting system Accessories Media, 6 modules, Dimensions: 53 mm x 138 mm x 63 mm	ZE335	1	piece

Categories

Low Voltage Products and Systems → Enclosures → Consumer Units → Consumer Units → UK600

