



PRODUCT-DETAILS

UK663CV

Combi Unit UK600 Combi, Flush-/ hollow wall mounting, 36 modules, 5 row(s), IP30, Door: Single, Steel Sheet, Dimensions: 872 mm x 384 mm x 97 mm



General Information	
Extended Product Type:	UK663CV
Product ID:	2CPX031399R9999
EAN:	4011617313991
Catalog Description:	Combi Unit UK600 Combi, Flush-/ hollow wall mounting, 36 modules, 5 row(s), IP30, Door: Single, Steel Sheet, Dimensions: 872 mm x 384 mm x 97 mm

Long Description:	Combi Unit, series UK600, Expansion option: Lateral and bottom, for the internal use, with closed doorframe and door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, Impact strength IK07, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, Powder-coated, in RAL 9016, enclosure out of thermoplast, with frame and ventilated door , door out of sheet steel, in RAL 9016, with TIP-in closure, door opening angle 120 degree, door hinge right or left, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 872 x 384 x 97, Shutter frame dimensions in mm (H x W x D): 872 x 384 x 9, Space units 36, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, with N/PE Quick-terminal, cable fastening rail integrated, assembled with device carrier, segregation wall, perforated sheet steel mounting plate and socket outlet, device support removable
Display Name:	UK663CV

Technical	
Number of Entrances:	Socket Outlet 0
Number of Rows:	5
Closure Type:	Push Button
Configuration Type:	assembled with device carrier, segregation wall, perforated sheet steel mounting plate and socket outlet
Cover Plate Type:	Door
Enclosure Type:	Combi Unit
Door Type:	Single
Accessories Available:	Yes
DIN Place Units:	36
Terminal Type:	Quick-Terminal
Impact Resistance Rating:	IK07

Electrical	
Rated Operational Voltage:	Maximum 400 V
Operational Voltage:	400 V
Rated Insulation Voltage (U _i):	690 V
Rated Impulse Withstand Voltage (U _{imp}):	6 kV
Rated Current (I _n):	63 A
Power Loss:	Δt = 30K - Enclosures 73 W

Design	
Surface Finishing:	Powder-coated
Housing Material:	Plastic
Door Material:	Steel Sheet
Cover Style:	Closed
RAL Number:	RAL 9016 - Traffic White
Color:	Traffic white

Number of Modules: 36

Material Compliance

RoHS Declaration:	2CPC100018X0201
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date:	20250929
REACH Declaration:	2CPC100005X0201
REACH Information:	False - does not contain substances > 0.1 mass percentage
REACH Date:	20260130
Conflict Minerals Reporting Template (CMRT):	9AKK108468A3363
WEEE Category:	4. Large Equipment (Any External Dimension More Than 50 cm)
WEEE B2C / B2B:	Business To Consumer

Environmental

Degree of Protection:	IP30
Protection Class:	Isolated (Class II)

Dimensions

Width in Number of Modular Spacings:	12
Product Net Width:	384 mm
Product Net Height:	872 mm
Product Net Depth / Length:	97 mm
Product Net Weight:	5.616 kg
Built-In Depth (t ₂):	88 mm
Dimension Diagram:	2CPC000001D0201 2CPC000004D0201 2CPC000005D0201 2CPC000007D0201

Engineering

Building Information Modeling – BIM:	9AKK107046A7947
--------------------------------------	-----------------

Ordering

Package Level 1 Units:	pack 1 piece
Package Level 1 Gross Weight:	5.841 kg
E-Number (Sweden):	2201248

Certificates and Declarations

Declaration of Conformity - CE: 2CPC100018X0201

Installation

Instructions and Manuals: 2CPC130100M5601
2CPC130110M5601

Mounting Type: Flush-/ hollow wall mounting

Popular Downloads

Data Sheet, Technical Information: 2CPC000001C0101
2CPC000002C0101

External Classifications and Standards

ETIM 9: EC000214 - Small distribution board

ETIM 10: EC000214 - Small distribution board

eClass: V11.0 : 27142409

Object Classification Code: U

Standards: DIN 43871

Accessories

Identifier	Description	Qty	Type	Unit Of Measure
2CPX062745R9999	Quick terminals terminals , blue , N/RDC Terminal , Quick-Terminal	1	ZK50BT	piece
2CPX030892R9999	Enclosure accessories UK600 / AK600 accessories, Direct mounting, IP30, Dimensions: 36 mm x 42 mm x 15 mm	1	ZK507	piece
2CPX031413R9999	Enclosure accessories UK600 / AK600 accessories, Door: Single, Dimensions: 43 mm x 59 mm x 41 mm	1	UZT4	piece
2CPX031412R9999	Enclosure accessories UK600 / AK600 accessories, Door: Single, Dimensions: 43 mm x 59 mm x 41 mm	1	UZT3	piece

2CPX031434R9999	Enclosure accessories UK600 accessories, Dimensions: 80 mm x 120 mm x 30 mm	1	UZ91P4	piece
2CPX031406R9999	Enclosure accessories UK600 accessories, 60 modules, 5 row(s), Dimensions: 872 mm x 384 mm x 90 mm	1	AP660	piece
2CPX061178R9999	Interior fitting system Accessories Media, Dimensions: 62 mm x 125 mm x 68 mm	1	ZX29	piece
2CPX061177R9999	Customized electrical components Accessories Media, Dimensions: 50 mm x 102 mm x 63 mm	1	ZE225	piece
2CPX031408R9999	Enclosure accessories UK600 accessories, Dimensions: 109 mm x 109 mm x 36 mm	1	UZB2	piece
2CPX061211R9999	Customized electrical components Accessories Media, Dimensions: 63 mm x 213 mm x 58 mm	1	ZE227	piece
2CPX031426R9999	Interior fitting system Accessories Media, Dimensions: 40 mm x 16 mm x 63 mm	1	ZE338	piece
2CPX031427R9999	Customized electrical components Accessories Media, Dimensions: 54 mm x 50 mm x 58 mm	1	ZE224	piece
2CPX031424R9999	Interior fitting system Accessories Media, 12 modules, Dimensions: 53 mm x 246 mm x 63 mm	1	ZE336	piece
2CPX031423R9999	Interior fitting system Accessories Media, 6 modules, Dimensions: 53 mm x 138 mm x 63 mm	1	ZE335	piece

Categories

Products > Low Voltage Products and Systems > Enclosures > Consumer Units > Consumer Units > UK600

